Issued to:	C3CONTROLS 664 STATE ST PO BOX 496 BEAVER, PA 15009-0496 United States
This is to certify that	NLDX7 - Motor Controllers, Magnetic Certified for Canada
representative samples of	See Addendum Page for Product Designation(s).
	Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	CSA C22.2 NO. 60947-4-1, 2nd Ed., Issue Date: 2014-04-04, Revised 2018-05
Additional Information:	See the UL Online Certifications Directory at <a href="https://iq.ulprospector.com">https://iq.ulprospector.com</a> for additional information

Olbrah Jenning - Corres Deborah Jennings-Conner, VP Regulatory Services UL LLC

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Debrah Jenning- Corne Deborah Jennings-Conner, VP Regulatory Services UL LLC



This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
300-S, followed by 09 or 12 or 18 or 25 or 32 or 40 may be followed by N followed by 30, 03, 40, 04, 20, 02, 22, 31 or 13 followed by characters related to coil voltage followed by 00, 01, 10, 11, 20, 02 or 22 may be followed by -WW.	Magnetic Motor Controllers
310-S series, followed by 09 or 12 or 18 or 25 or 32 or 40 may be followed by N followed by 30, 03, 40, 04, 20, 02, 22, 31 or 13 followed by characters related to coil voltage followed by 00, 01, 10, 11, 20, 02 or 22 may be followed by -WW.	Magnetic Motor Controllers
Accessory for contactor, wiring module Type 300 followed by RWS followed by 025 or 040.	Magnetic Motor Controllers
Surge suppresser Type 300-S followed by RCS followed by 2 followed by J or AH or M.	Magnetic Motor Controllers

Debrah Jenning-Corner Deborah Jennings-Conner, VP Regulatory Services UL LLC



Issued to:	C3CONTROLS 664 STATE ST PO BOX 496 BEAVER, PA 15009-0496 United States
This is to certify that representative samples of	NLDX - Motor Controllers, Magnetic See Addendum Page for Product Designation(s).
	Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	UL 60947-4-1, 3rd Ed., Issue Date: 2014-04-04, Revision Date: 2017-10-17
Additional Information:	See the UL Online Certifications Directory at <a href="https://iq.ulprospector.com">https://iq.ulprospector.com</a> for additional information

Olbrah Jenning - Crene-Deborah Jennings-Conner, VP Regulatory Services UL LLC

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Debrah Jenning- Corne Deborah Jennings-Conner, VP Regulatory Services UL LLC



This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
300-S, followed by 09 or 12 or 18 or 25 or 32 or 40 may be followed by N followed by 30, 03, 40, 04, 20, 02, 22, 31 or 13 followed by characters related to coil voltage followed by 00, 01, 10, 11, 20, 02 or 22 may be followed by -WW.	Magnetic Motor Controllers
310-S series, followed by 09 or 12 or 18 or 25 or 32 or 40 may be followed by N followed by 30, 03, 40, 04, 20, 02, 22, 31 or 13 followed by characters related to coil voltage followed by 00, 01, 10, 11, 20, 02 or 22 may be followed by -WW.	Magnetic Motor Controllers
Accessory for contactor, wiring module Type 300 followed by RWS followed by 025 or 040.	Magnetic Motor Controllers
Surge suppresser Type 300-S followed by RCS followed by 2 followed by J or AH or M.	Magnetic Motor Controllers

Debrah Jenning-Corner Deborah Jennings-Conner, VP Regulatory Services UL LLC

