

CERTIFICATE OF COMPLIANCE

Certificate Number 20140224-E68568

Report Reference E68568-19941024

Issue Date 2014-February-24

Issued to: C3CONTROLS
664 STATE ST
PO BOX 496
BEAVER PA 15009

**This is to certify that
representative samples of** AUXILIARY DEVICES
See Addendum Page


Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL508, Industrial Control Equipment.
CSA C22.2 No. 14-13, Industrial Control Equipment.

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and

"US" identifiers:  the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20140224-E68568

Report Reference E68568-19941024

Issue Date 2014-February-24

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models:

Indicating lights, Cat. Nos. FV, FVLU, RL, RLU, RTL, TF, TFLU, with or without prefix H, may be followed by blank, AC, MI, PPM, PTR, or PTT, may be followed by blank or any number from 0 to 600, may be followed by blank or D, may be followed by blank, I, L or N, may be followed by blank or any number from 0 to 600, may be followed by blank, A, B, C, G, F, NL, R, W or Y, may be followed by blank, A, HRB, RB, RB4, or Y, may be followed by blank, GIPBC, IMC, IPBC, IPBCM, PLL, PTR, or SIPBCM, may be followed by blank, AR, BE, BET, BK, CR, GN, GNT, GY, OE, RD, RDT, WE or YW, may be followed by blank, AAB, DB, EM, NC, NC/NC, NO/NC, NO, NO/NO, PRDB, PREM, PRNC, PRNO, PR2NC, PR2NO, PRNOEM, PRNONC, may be followed by any multiple combination of the previous, may be followed by G, may be followed by blank or IP20.

Pushbuttons, Cat. Nos. PBO, with or without prefix H, may be followed by blank, A, HRB, RB, RB4, or Y, may be followed by blank, FC, GFC, GXC, JMC, MC, SJC, SMC or XC, may be followed by blank, AR, BE, BET, BK, CR, GN, GNT, GY, OE, RD, RDT, WE or YW, may be followed by blank, AAB, DB, EM, NC, NC/NC, NO, NO/NC, NO/NO, PRDB, PREM, PRNC, PRNO, PRNOEM, PRNONC, PR2NC or PR2NO, may be followed by any multiple combination of the previous, may be followed by G, may be followed by blank or IP20.

Linear actuated devices, Cat. Nos. Blank, CPO, HDCPO, PBO, PPCPO, or PTR, with or without prefix H, may be followed by blank, A, HRB, RB, RB4, or Y, may be followed by blank, PM or PP, may be followed by blank, FC, JMC, MC, TMC, or XC, may be followed by blank, AC or MI, may be followed by blank, AR, BE, BET, BK, CR, GN, GNT, GY, OE, RD, RDT, WE, YW, may be followed by blank, AAB, DB, EM, NC, NC/NC, NO, NO/NC, NO/NO, PRDB, PREM, PRNC, PRNO, PRNOEM, PRNONC, PR2NC or PR2NO, may be followed by any multiple combination of the previous, may be followed by G, may be followed by blank or IP20.

Rotary switches, Cat. Nos. SROL, SROLR, SROR, SROLR, SRORL, SS02, SS03, SS04, SS043, SS01243, with or without prefix H, may be followed by blank, A, HRB, RB, RB4, or Y, may be followed by blank, CSO, SH or SL; may be followed by blank, AR, BE, BET, BK, CR, GN, GNT, GY, OE, RD, RDT, WE or YW, may be followed by blank, AAB, DB, EM, NC, NC/NC, NO, NO/NC, NO/NO, PR2NC, PR2NO, PRDB, PREM, PRNC, PRNO, PRNOEM or PRNONC; may be followed by any multiple combination of the previous, may be followed by G, may be followed by blank or IP20.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20140224-E68568

Report Reference E68568-19941024

Issue Date 2014-February-24

Rotary key switches, blank, A, HRB, RB, RB4, or Y, followed by KOSRLC, KOSRLRC, KOSRRC, KOSRLR, KOSRRL, KSROR3LC, KOSS2, KOSS3, KOSS4, KSROR3LRC, KSROR3RC or KSSOR3, with or without prefix H; may be followed by blank, KA, KC, KL, KLC, KLR, KR, KRC, may be followed by blank, AAB, DB, EM, NC, NC/NC, NO, NO/NC, NO/NO, PR2NC, PR2NO, PRDB, PREM, PRNC, PRNO, PRNOEM, PRNONC, may be followed by any multiple combination of the previous, may be followed by G, may be followed by blank or IP20.

Potentiometer operators, Cat. No. POTO, with or without prefix H, may be followed by blank, A, HRB, RB, RB4, or Y, may be followed by blank or any number from 0 to 999, may be followed by blank, K or M, may be followed by blank or TBW.

Wobble stick operators, Cat. Nos. WS, with or without prefix H, may be followed by blank, A, HRB, RB, RB4, or Y, may be followed by blank, AAB, DB, EM, NC, NC/NC, NO, NO/NC, NO/NO, PRDB, PREM, PRNC, PRNO, PRNOEM, PRNONC, PR2NC, or PR2NO, may be followed by any multiple combination of the previous, may be followed by G, may be followed by blank or IP20.

Reset pushbutton, Cat. No. RPB, with or without prefix H, may be followed by B, BW, BOLTS, W, or WASHERS.

Pilot Lights Cat. No. 30MV12-277, 30MV20-277, or 30RMV12-277, or 30RMV20-277 followed by FL or DL followed by either A, B, G, R, C or W may be followed by PLLRD, PLLAR, PLLGN, PLLWE, PLLBE, PLLCR, APLLRD, APLLAR, APLLGN, APLLWE, APLLBE or APLLCR.

Accessories, designated blank, HP or IP20.

(+) Prefix H indicates use of stainless steel screws in construction.

(++) Suffix G indicates contacts may be plated with gold.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

