

NKJH.E312106 - Combination Motor Controllers

Combination Motor Controllers

See General Information for Combination Motor Controllers

C3CONTROLS

664 STATE ST
PO BOX 496
BEAVER, PA 15009 USA

E312106

Investigated to ANSI/UL 60947-1 and ANSI/UL 60947-4-1

Open type Front mount mounted Auxiliary contact block Model(s) 330-FA11S25

Accessory Open type Model(s) Front mount mounted Auxiliary contact block model no. 330-FA11S25

Open type Indicator Auxiliary Contact block Model(s) 330-STA22S25

Indicator Auxiliary Contact block model no. 330-STA22S25

Open type Side Mounted Auxiliary Contact Block Model(s) 330-SA02S25, 330-SA11S25, 330-SA20S25

Side Mounted Auxiliary Contact Block Model no. 330-SA11S25, 330-SA02S25, 330-SA20S25

Open type, Manual self-protected combination motor controllers, Type E Model(s) "300-S Series" Model No(s). 330-T25S2C16, 330-T25S2C25, 330-T25S2C40, 330-T25S2C63, 330-T25S2D10, 330-T25S2D16, 330-T25S2D25, 330-T25S2D40, 330-T25S2D63 330-T25S2U10, 330-T25S2U16, 330-T25S2U20, 330-T25S2U25, 330-T25S2U32

Open type, Self-protected combination motor controllers, Type E Model(s) 330-T25S2C16, 330-T25S2C25, 330-T25S2C40, 330-T25S2C63, 330-T25S2D10, 330-T25S2D16, 330-T25S2D25, 330-T25S2D40, 330-T25S2D63, 330-T25S2U10, 330-T25S2U16, 330-T25S2U20, 330-T25S2U25, 330-T25S2U32

Type F Combination Motor Controller. "330-T25 Series" when used with c3Controls 300-S series contactors; Model(s). 330-T25S2C16, 330-T25S2C25, 330-T25S2C40, 330-T25S2C63, 330-T25S2D10, 330-T25S2D16, 330-T25S2D25, 330-T25S2D40, 330-T25S2D63 330-T25S2U10, 330-T25S2U16, 330-T25S2U20, 330-T25S2U25, 330-T25S2U32

Last Updated on 2020-03-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"