

1/8" 3
 3/16" 2
 1/4" 1
 * REMOVE ONE ADDITIONAL GASKET
 WHEN USING A LEGEND PLATE


CLAMP RING
(PLASTIC OR ALUMINUM)

HOUSING

CONTACT
BLOCKS

GASKETS

PUSH BUTTON
CAP



NOTES:

- 1) MOUNTING HOLE IN PANEL - $\phi 1-3/16$ (30MM)
- 3) MOUNTING HOLE SPACING (FOR STANDARD LEGEND PLATES) - HORIZONTAL & VERTICAL DISTANCE - 2.250 CENTER TO CENTER
- 2) CHOICE OF ALUMINUM OR PLASTIC CLAMP RING (NEMA 4 OR NEMA 4X).

XXX	XXXXXXXXXX	XXXX	XXX	30MM PRODUCT LINE FULL VOLTAGE ILLUMINATED PUSH BUTTON DATA SHEET	
XXX	XXXXXXXXXX	XXXX	XXX		
XXX	XXXXXXXXXX	XXXX	XXX		
XXX	XXXXXXXXXX	XXXX	XXX		
XXX	XXXXXXXXXX	XXXX	XXX		
XXX	XXXXXXXXXX	XXXX	XXX		
REV	DESCRIPTION	DATE	BY	DRAWN BY: RCG	DATE: 09-06-01



CONTROL CONCEPTS CORP.

P.O. BOX 496
664 STATE STREET
BEAVER, PA 15009



SCALE:
1:1

DRAWING NO.
WC100076