



PART NUMBER	PTB 115-1	PTB 175-1	PDB 115-1
APPROVALS	CSA-c / us	CSA-c / us	CSA-c / us
CURRENT RATING (PER POLE)	115A Cu / Al	175A Cu / Al	115A Cu / Al
VOLTAGE RATING (PER POLE)	600V AC/DC	600V AC/DC	600V AC/DC
POLES (LINE / LOAD)	1-Line / 1-Load	1-Line / 1-Load	1-Line / 4-Load
NUMBER OF POLES	1	1	1
FLAMABILITY	94V-0	94V-0	94V-0
WIRE TORQUE	Line Side-50 in/lbs (MAX) Load Side-50 in/lbs (MAX)	Line Side-100 in/lbs (MAX) Load Side-100 in/lbs (MAX)	Line Side-50 in/lbs (MAX) Load Side-25 in/lbs (MAX)
WIRE RANGE	Line Side - #2 to #14 Load Side - #2 to #14	Line Side - 2/0 to #8 Load Side - 2/0 to #8	Line Side - #2 to #14 Load Side - #8 to #1
CONNECTOR MATERIAL	AL (electrotin plate)	AL (electrotin plate)	AL (electrotin plate)
DIMENSIONS	0.75W x 3.0L x 1.95H	0.85W x 3.0L x 2.15H	0.75W x 3.0L x 1.95H
MOUNTING SPECIFICATIONS	For Panel Mounting: Recommend Use Of #10 Pan Head Screw Using 5-10 CAUTION: If Using A Smaller Size Or Different Head Style, Use A Flat Washer The Molded Base.		

TECHNICAL SPECIFICATIONS