

XCFR2.E145984 - Terminal Blocks - Component

Terminal Blocks - Component

See General Information for Terminal Blocks - Component

C3CONTROLS664 STATE ST
PO BOX 496
BEAVER, PA 15009 USA

E145984

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
HDTB-4, HDTB-6, and HDTB-12	18-10, SOL/ STR	Cu	2	18 - 20	600	30	B, C	2 (105),4
WTB2-W2	22-12, SOL/STR	Cu	2	7	600	20(1)	B,C	2 (105),4
WTB2-W4	22-10, SOL/ STR	Cu	2	7	600	30(2)	B,C	2 (105),4
WTB2-W6	22-8, SOL/STR	Cu	2	9	600	50	B,C	2 (105),4
WTB2-W10	18-6, STR	Cu	2	14	600	65	B,C	2 (105),4
WTB2-W16	16-4, STR	Cu	2	14	600	85	B,C	2 (105),4
WTB2-W25	14-3, STR	Cu	2	14	600	100(3)	B,C	2 (105),4
WTB2-W35	8-2, STR	Cu	2	25	600	115(4)	B,C	2 (105),4
WTB2-FB52	22-10, SOL/STR	Cu	2	7	600	10	B,C	2 (105),4,@
WTB2-FB52L	22-10, SOL/STR	Cu	2	7	600	10	B,C	2 (105),4,@
WTB2-FB52DB	22-10, SOL/STR	Cu	2	7	600	16	B,C	2 (105),4,@
WTB2-W70	2/0-6, STR	Cu	2	60	600	150	B,C	2 (105), 4
WTB2-W95	4/0-2, STR	Cu	2	160	600	230	B,C	2 (105), 4
WTB2S-W2	22-14, SOL/STR	Cu	1,2	N/A (6)	600	15 (5)	B,C	2 (105), 4
WTB2S-W2-12	22-14, SOL/STR	Cu	1,2	N/A (6)	600	15 (5)	B,C	2 (105), 4
WTB2S-W2-22	22-14, SOL/STR	Cu	1,2	N/A (6)	600	15 (5)	B,C	2 (105), 4
WTB2S-MW2	22-14, SOL/STR	Cu	1,2	N/A (6)	600	15 (5)	B,C	2 (105), 4

WTB2S-MW2-22	22-14, SOL/STR	Cu	1,2	N/A (6)	600	15 (5)	B,C	2 (105), 4
WTB2S-W4	22-12, SOL/STR	Cu	1,2	N/A (6)	600	20 (1)	B,C	2 (105), 4
WTB2S-W4-12	22-12, SOL/STR	Cu	1,2	N/A (6)	600	20 (1)	B,C	2 (105), 4
WTB2S-W4-22	22-12, SOL/STR	Cu	1,2	N/A (6)	600	20 (1)	B,C	2 (105), 4
WTB2S-W6	22-8, SOL/STR	Cu	2	N/A (6)	600	50	B,C	2 (105), 4
WTB2S-W6-12	22-8, SOL/STR	Cu	2	N/A (6)	600	50	B,C	2 (105), 4
WTB2S-W6-22	22-8, SOL/STR	Cu	2	N/A (6)	600	50	B,C	2 (105), 4
WTB2-FB1	22-10 Sol/Str	Cu	2	7	600	16	B,C	2(105),4, @
WTB2-FB1L	22-10 Sol/Str	Cu	2	7	600	16	B,C	2(105),4, @
WTB2-FB130-NF	20-6 Str	Cu	2	14	600	30	B,C	2(105),4, @
WTB2-FB130L110A-NF	20-6 Str	Cu	2	14	600	30	B,C	2(105),4, @
WTB2-PDB80	8-4 Str*, 8-4 Str**	Cu	2	14	600	80	B,C	2(105),4
	14-10 Str**			7		30		

Note: * represents - Input and Double

Note: ** represents - Output (any combination of output can be connected one at a time)

Note: @ Terminal blocks are intended for use with miscellaneous fuses

Note: (1) - 25 A max. for factory-wiring only

Note: (2) - 35 A max. for factory-wiring only

Note: (3) - 115 A max. for factory-wiring only

Note: (4) - 145 A max. for factory-wiring only

Note: (5) - 20A max. for factory wiring only

Note: (6) - Spring Force Connection Type Terminal Block

Note A - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.

DTB/DRDTB Series	22-12	Cu	2	20	600	15	B, C	2(110),#
FTB/DRFTB-6 Series	22-12	Cu	2	12	600	25	B, C	2(110),4
MTB/DRTB/DR-25 Series	22-12	Cu	2	12	600	25	B, C	2(110),4
MTB/DRTB/DR-50 Series	16-8	Cu	2	20	600	50	B, C	2(110),4
WTB-FB52L	26-8	Cu	2	0.8	300	6.3	B,C,D	2(105),4
WTB-FB52	26-8	Cu	2	0.8	300	6.3	B,C,D	2(105),4
WTB-FB52DB	26-8	Cu	2	0.8	300	6.3	B,C,D	2(105),4
WTB-DB4	26-10	Cu	2	0.5	600	16	B,C,D	2(105),4#
WTB-W4 with suffixes	26-10	Cu	2	0.5	300	30	B,C,D	2(105),4
DD, DDB, DDD, DDL (1)								
Note: (1) 32A for factory wiring.								
WTB-DB10	8-16	Cu	2	1.2	600	50	B,C,D	2(105),4
WTB-W2	26-12	Cu	2	0.4	600	20	B,C	2(105),4
WTB-W4	26-10	Cu	2	0.5	600	30	B,C,D	2(105),4
WTB-W6	26-8	Cu	2	0.8	600	50	B,C,D	2(105),4
WTB-W10	16-6	Cu	2	1.2	600	65	B,C,D	2(105),4
WTB-W16	12-4	Cu	2	1.2	600	85	B,C	2(105),4
WTB-W35	10-2	Cu	2	2.0	600	115	B,C	2(105),4
WTB-W70	6-2/0	Cu	2	6.0	600	175	B,C	2(105),4
WTB-W2/4G	26-10	Cu	2	0.5	—	—	—	2(105),4
WTB-W6/10G	16-8	Cu	2	1.2	—	—	—	2(105),4
WTB-W2T, -W4DDG, -W2TG	24-12	Cu	2	0.4	300,300,600	24	B,C,D	2(105),4

PCTB Terminal Blocks

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
WTB2-W6/10G	16-6, STR	Cu	2	14	600	N/A	B,C	2 (105),4
WTB2-W2/4G	22-10, SOL/STR	Cu	2	7	600	N/A	B,C	2(105),4
WTB2-W16/35G	8-2, STR	Cu	2	25	600	N/A	B,C	2(105),4
WTB2S-W2G	22-14, SOL/STR	Cu	2	N/A (6)	600	N/A	B,C	2(105),4
WTB2S-W4G	22-12, SOL/STR	Cu	2	N/A (6)	600	N/A	B,C	2(105),4
WTB2S-W6G	22-8, SOL/STR	Cu	2	N/A (6)	600	N/A	B,C	2(105),4

Note: (6) - Spring Force Connection Type Terminal Block

#Device is not to be switched under load. Marking required.

Marking: Company name and catalog designation. (Catalog designation may be marked on shipping carton).

Last Updated on 2018-12-26

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"